





SIDE ELEVATION


END ELEVATION

NOTES:

- FRAMEWORK TO BE WELDED AND MECHANICALLY FASTENED STEEL
- ALL FASTENERS TO BE STAINLESS STEEL
- ROOF GLAZING TO BE: 8MM POLYCARBONATE STRUCTURED SHEET, TONGUE AND GROOVE SYSTEM, IN ALUMINUM TRIM. TINT: STEEL FINISHING:
- MEDIA BLAST PREP
- TNEMEC TNEME ZINC 90-97 PRIMER
- TNEMEC SERIES N69 H-BUILD EPOXYLINE 2-PART EPOXY MIDCOAT: TNEMEC SERIES 73 ENDURA-SHIELD TOPCOAT. ALUMINUM TRIM TO HAVE SAME TOP TWO COATS (OR IN MATCHING ANODIZED). COLOR: _____
- ALL DIMENSIONS TO BE FIELD VERIFIED
- DESIGN IS PRELIMINARY, AND CONCEPTUAL, AND SUBJECT TO CHANGE BASED ON FINAL ENGINEERING PHASE AND CUSTOMER APPROVAL.



PLAN VIEW
(36" RACK SPACING)



PLAN VIEW
(30" RACK SPACING)

© Design by Duo-Gard Industries, Inc., 2010



THIS DRAWING IS PROPRIETARY AND FOR THE SOLE USE OF OUR CUSTOMER AND MAY NOT BE COPIED OR REPRODUCED WITHOUT PRIOR WRITTEN CONSENT FROM DUO-GARD INDUSTRIES, INC. LEAD TIME BEGINS UPON RECEIPT OF SIGNED SHOP DRAWINGS.

APPROVAL SIGNATURE

DATE

X

PROJECT NAME

CUSTOMER SAMPLE

DESCRIPTION

9' x 9' "APEX" BICYCLE SHELTER, PLAN AND ELEVATION DETAILS

PRJ ENG	PRJ MGR	DRFTR	DRWG DATE	REV1	REV2	SCALE	PAGE	OF	DRWG #
BDI	SM	GS	12.17.2014			3/16" = 1'-0"	1	1	913APEX

BIKE DOCK CAPACITY		
RACK SPACING	# OF RACKS	# OF BIKES
36"	3	6
30"	3	6